

TECHNICAL SHEET

SIATA COMMERCIAL VALVE V230





SIATA COMMERCIAL VALVE - V230

TECHNICAL CHARACTERISTICS



- Flow rate: up to 8.5 m³/h
- Quick connect clips allowing easy installation and maintenance
- Hydraulically actuated
- Internal turbine option for meter control
- Driver replica of the pressure point for any special applications, such as driving an external brine valve or closing the valve outlet
- Suitable for simplex, duplex or multiplex softening systems, as well as for filtration, demineralisation, dealkalisation or iron & manganese removal applications
- Compatible with the entire SIATA controller range

TECHNICAL SPECIFICATIONS

VALVE SPECIFICATIONS

| | |
|----------------------|---------------------------|
| Material | Glassfiber reinforced ABS |
| Color | Blue or black |
| Hydrostatic pressure | 22 bar |
| Working pressure | 1.5-6 bar |
| Working temperature | 5-40°C |

FLOW RATE (3.5 bar inlet - valve alone)

| | |
|---|-----------------------|
| Continuous ($\Delta p = 1$ bar) | 8.5 m ³ /h |
| Peak ($\Delta p = 1.9$ bar) | 11 m ³ /h |
| Cv* | 9.6 gpm |
| Maximum backwash ($\Delta p = 1.9$ bar) | 4 m ³ /h |
| Maximum rapid rinse ($\Delta p = 1.9$ bar) | 4.5 m ³ /h |

* Cv: Flow rate of valve alone in gpm at 0.07 bar pressure drop.

DOWN FLOW REGENERATION

| | |
|-------------------|--------------------------------|
| Adjustable cycles | Depending on controller fitted |
|-------------------|--------------------------------|



VALVE CONNECTIONS

| | |
|---------------------------|----------------------------|
| Inlet/Outlet | male 2 inches BSP threaded |
| Distributor pipe | DN 50 |
| Drain line | 20 mm - QC** |
| Brine line | 3/8 inch BSP |
| Mounting base | 4 inches BSP threaded |
| Height (from top of tank) | 129 mm ± 2 |

** QC: Quick connect

TANK SIZE APPLICATION (recommended)

| | |
|------------------|---|
| Water softener | 8 - 21 inches (max 300 L of resin) |
| Filter | 8 - 21 inches (according to filter media specs) |
| Demineralisation | 8 - 21 inches (max 300 L of resin) |

METER

| | |
|----------------------------------|--------------|
| Internal: | |
| Accuracy range (± 5%) | 12 - 200 Lpm |
| External: | |
| Accuracy range 3/4 inch (± 5%) | 10 - 120 Lpm |
| Accuracy range 1 1/2 inch (± 5%) | 12 - 200 Lpm |

REGENERATION CYCLES

| | |
|-----------------------------|-----------------------------------|
| Softener & Demineralisation | 1) Backwash (Upflow) |
| | 2) Brine & slow rinse (Down flow) |
| | 3) Rapid rinse (Down flow) |
| Filter*** | 1) Backwash (Upflow) |
| | 2) Rapid rinse (Down flow) |

*** Depending on the controller type brine draw and slow rinse time must be set on 0.

OPTIONS

| | |
|------------------------------------|-----|
| Remote Bypass w/ or w/o sample tap | Yes |
| Driver replica | Yes |